



## TE-RH 38 E

Rotary Hammer

Art.-No.: 4257950

Ident-No.: 11013

The rotary hammer TE-RH 38 E with pneumatic hammer mechanism is a high-quality and versatile powerhouse for challenging construction, renovation and chiseling jobs. With hammer drilling as well as chiseling with and without chisel fixation this all-rounder is equipped with the three functions for the universal application. The main grip of the rotary hammer is vibration-absorbing and signals the optimal contact pressure via "Press Control" - an important support for low attrition and quick operations, though. The aluminium gear head of the rotary hammer is constructed robustly. Additionally, 2 LEDs inform about the remaining performance and needs of maintenance by attrition of brushes. Delivery in a practical transport and storage case.

### Features

- Hammer drill with pneumatic hammer action for very good drilling
- Robust SDS-Max tool chuck
- 3 functions: hammer drilling, chiseling with and without fixation
- Press-control: visualizes the optimum pressure
- Speed electronics for smooth initial drilling
- Low vibrations thanks to vibration-absorbing main handle
- Soft grip inserts also have a vibration-absorbing impact
- 2 status LEDs: ready for operation and service (brush wear)
- High-grade components for prolonged operation
- Aluminium gear head - light but robust
- Overload slip coupling for safety
- Infinitely adjustable drilling depth stop made of solid metal
- Additional handle with ribs for secure fastening
- Delivered in a practical case

### Technical Data

• Mains supply	220-240 V   50 Hz
• Power	1050 W
• Idle speed	0-500 min <sup>-1</sup>
• Impact rate	0-4100 min <sup>-1</sup>
• Impact power	9 J
• Tool holder	SDS Max
• Drilling capacity in concrete	38 mm



### Logistic Data

• Product weight	6.9 kg
• Gross weight single packaging	9.3 kg
• Dimensions single packaging	445 x 130 x 370 mm
• Pieces per export carton	2 Pieces
• Gross weight export carton	18.6 kg
• Dimensions export carton	365 x 455 x 275 mm
• Container quantity (20"/40"/40"HC)	1150   2350   2850

Illustrations can contain accessories, which are not included in standard extent of delivery  
Illustration similar (in design), production-wise modifications reserved  
GS mark belongs to the product itself only, excluded accessory

